

Description

The 4310 fused magnet safety disconnect switch is designed to safely allow the operator of a lifting magnet to disconnect the highly inductive magnet while the magnet is still energized. Standard safety switches are not designed to safely disconnect an energized magnet.

The 4310 has (3) power poles. Two normally open power poles to disconnect the incoming power and a third normally closed power pole that shunts the magnets energy into a discharge resistor when the disconnect is switched to the off position.

Features

- Supplied in a NEMA type 3R wall mounting enclosure.
- Rated 300 VDC. Max
- All switches have a padlockable thru-the-door operator
- High capacity discharge resistor



Part Number	Fused At	Magnet Amps (Max)	Enclosure Dimensions			List Price E43
			H	W	D	
4310-86262-004	100 Amps	67	29.00	12.63	10.00	\$1,900.00
4310-86262-002	200 Amps	134	29.00	12.63	10.00	\$2,250.00
4310-86273-001	400 Amps	267	31.25	24.00	13.29	\$6,130.00

How To Order

Specify magnet operating current, cold.

Enclosure type is NEMA 3R

Order by part number



Hubbell Industrial Controls, Inc.

A subsidiary of Hubbell Incorporated

4301 Cheyenne Dr., Archdale, NC. 27262

Telephone (336) 434-2800 • FAX (336) 434-2803

<http://www.hubbell-icd.com>

Sales@hubbell-icd.com